



HOSE

PROJET® 3000 3000 PSI Pressure Wash

Tube: Seamless, black synthetic rubber
Reinforcement: One braid of high tensile steel wire
Cover: Smooth abrasion & weather resistant synthetic rubber, Blue
Temperature: -40°C to +121°C/149°C Intermittent (-40°F to +250°F/300° Intermittent)
Packaging: 50' 100' 150' 200' Bulk Reels
Application: Pressure wash equipment



PART NUMBER	COVER	HOSE O.D.			MAXIMUM WORKING PRESSURE (psi)	MINIMUM BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE COUPLINGS
		HOSE I.D. (in)	(in)	(mm)		(in)	(mm)		
PJ3-08BLM	Smooth	1/2	0.75	19.0	3,000	5.5	140	0.32	E

*Not For Steam Service

PROJET® 4000 4000 PSI Pressure Wash

Tube: Seamless, black synthetic rubber
Reinforcement: One braid of high tensile steel wire
Cover: Wrapped abrasion & weather resistant synthetic rubber, Black, Blue or Gray
Temperature: -40°C to +121°C/149°C Intermittent (-40°F to +250°F/300° Intermittent)
Packaging: 50' 100' 150' 200' Bulk Reels
Application: Pressure wash equipment



PART NUMBER	COVER	HOSE O.D.			MAXIMUM WORKING PRESSURE (psi)	MINIMUM BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE COUPLINGS
		HOSE I.D. (in)	(in)	(mm)		(in)	(mm)		
PJ4-06BK	Wrapped	3/8	0.61	15.5	4,000	3.5	90	0.17	E
PJ4-06BL	Wrapped	3/8	0.61	15.5	4,000	3.5	90	0.17	E
PJ4-06GY	Wrapped	3/8	0.61	15.5	4,000	3.5	90	0.17	E

*Not For Steam Service

PROJET® 4000 4000 PSI Pressure Wash

Tube: Seamless, black synthetic rubber
Reinforcement: One braid of high tensile steel wire
Cover: Smooth abrasion & weather resistant synthetic rubber, Blue
Temperature: -40°C to +121°C/149°C Intermittent (-40°F to +250°F/300° Intermittent)
Packaging: 50' 100' 150' 200' Bulk Reels
Application: Pressure wash equipment



PART NUMBER	COVER	HOSE O.D.			MAXIMUM WORKING PRESSURE (psi)	MINIMUM BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE COUPLINGS
		HOSE I.D. (in)	(in)	(mm)		(in)	(mm)		
PJ4-04BLM	Smooth	1/4	0.48	12.2	4,000	2.9	75	0.19	E
PJ4-06BLM	Smooth	3/8	0.61	15.5	4,000	3.5	90	0.24	E

*Not For Steam Service

ULTRAJET® 4000 Oil Resistant Pressure Wash

- Tube: Seamless, black synthetic rubber
- Reinforcement: One braid of high tensile steel wire
- Cover: Yellow smooth ultra abrasion resistant synthetic rubber, RMA Class A
- Temperature: -40°C to +121°C (-40°F to +250°F)
- Packaging: 50' 100' 150' 200' Bulk Reels
- Application: Pressure Wash equipment where maximum abrasion or oil/fat resistance is required



PART NUMBER	COVER	HOSE I.D.		HOSE O.D.		MAXIMUM WORKING PRESSURE	MINIMUM BEND RADIUS		WEIGHT	ONE PIECE COUPLINGS
		(in)	(mm)	(in)	(mm)		(in)	(mm)		
UJ4-06YWM	Smooth	3/8	15.5	0.61	15.5	4,000	3.5	90	0.24	E

*Not For Steam Service

SUPERJET® 6000 6000 PSI Pressure Wash

- Tube: Seamless, black synthetic rubber
- Reinforcement: Two braids of high tensile steel wire
- Cover: Wrapped abrasion & weather resistant synthetic rubber, Black, Blue or Gray
- Temperature: -40°C to +121°C/149°C Intermittent (-40°F to +250°F/300° Intermittent)
- Packaging: 50' 100' 150' 200' Bulk Reels
- Application: Pressure wash equipment



PART NUMBER	COVER	HOSE I.D.		HOSE O.D.		MAXIMUM WORKING PRESSURE	MINIMUM BEND RADIUS		WEIGHT	ONE PIECE COUPLINGS
		(in)	(mm)	(in)	(mm)		(in)	(mm)		
SJ6-06BK	Wrapped	3/8	17.1	0.673	17.1	6,000	3.5	90	0.29	E
SJ6-06BL	Wrapped	3/8	17.1	0.673	17.1	6,000	3.5	90	0.29	E
SJ6-06GY	Wrapped	3/8	17.1	0.673	17.1	6,000	3.5	90	0.29	E

*Not For Steam Service

SUPERJET® 6000 6000 PSI Pressure Wash

- Tube: Seamless, black synthetic rubber
- Reinforcement: Two braids of high tensile steel wire
- Cover: Smooth abrasion & weather resistant synthetic rubber, Blue
- Temperature: -40°C to +121°C/149°C Intermittent (-40°F to +250°F/300° Intermittent)
- Packaging: 50' 100' 150' 200' Bulk Reels
- Application: Pressure wash equipment



PART NUMBER	COVER	HOSE I.D.		HOSE O.D.		MAXIMUM WORKING PRESSURE	MINIMUM BEND RADIUS		WEIGHT	ONE PIECE COUPLINGS
		(in)	(mm)	(in)	(mm)		(in)	(mm)		
SJ6-06BLM	Smooth	3/8	17.1	0.673	17.1	6,000	3.5	90	0.29	E
SJ6-08BLM	Smooth	1/2	20.7	0.81	20.7	6,000	5.1	130	0.39	E

*Not For Steam Service