

## DV10 TPR-W



**Tube:** Thermoplastic rubber hose  
**Reinforcement:** Steel wire helix  
**Cover:** Thermoplastic rubber hose with external orange polypropylene wearstrip  
**Temperature:** -51°C to +135°C (-60°F to +275°F; Intermittent to +300°F)  
**Application:** A wire reinforced, TPR elastomer with a wear strip, with good resistance to abrasion, chemicals, and weathering. Smooth interior assures minimal friction loss and efficient air flow. Excellent low and high temperature properties make this a truly versatile indoor/outdoor ducting. For general dust and fume extraction, sawdust, and other mildly abrasive powders.

Part Number	ID (in)	Max WP (psi)	Vacuum (hg)	Bend Radius (in)	Weight (lb/ft)	Standard Pack
DV10-200	2	19	29"	3.5	0.25	25'- Coil
DV10-250	2-½	14	28"	4.0	0.35	25'- Coil
DV10-300	3	11	28"	4.3	0.40	25'- Coil
DV10-350	3-½	10	25"	5.3	0.50	25'- Coil
DV10-400	4	9	25"	6.5	0.67	25'- Coil
DV10-500	5	8	15"	8.0	0.85	25'- Coil
DV10-600	6	7	11"	8.8	0.87	25'- Coil
DV10-700	7	5	9"	10.0	1.00	25'- Coil
DV10-800	8	4.5	5.5"	12.0	1.20	25'- Coil
DV10-1000	10	4	5"	12.5	2.20	25'- Coil
DV10-1200	12	3	4"	13.7	2.70	25'- Coil
DV10-1400	14	2	2"	18.0	3.00	25'- Coil

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

## DV20 URETHANE CLEAR - MD



**Tube:** Clear polyurethane  
**Reinforcement:** Bronze coated spring steel wire helix  
**Cover:** Clear polyurethane  
**Temperature:** -53°C to +93°C (-63°F to +199°F)  
**Application:** A wire reinforced three ply polyurethane duct with excellent abrasion resistance, low temperature and chemical resistance. LD version available for lighter duty applications and HD version available for extra abrasion and puncture resistance.

Part Number	ID (in)	Max WP (psi)	Vacuum (hg)	Bend Radius (in)	Weight (lb/ft)	Standard Pack
DV20-200	2	30	29"	3.0	0.25	25' - Coil
DV20-250	2-½	30	29"	4.0	0.32	25' - Coil
DV20-300	3	29	29"	5.0	0.40	25' - Coil
DV20-400	4	25	29"	6.5	0.70	25' - Coil
DV20-500	5	22	17"	7.5	0.90	25' - Coil
DV20-600	6	19	15"	8.5	1.00	25' - Coil
DV20-700	7	16	12"	10.5	1.20	25' - Coil
DV20-800	8	14	9"	12.0	1.50	25' - Coil
DV20-1000	10	11	4"	14.0	1.60	25' - Coil
DV20-1200	12	10	2.2"	16.0	2.00	25' - Coil
DV20-1400	14	8	3.3"	18.0	2.50	25' - Coil

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.



## DV30 STANDARD VAC (Z VAC)

**Cover:** Grey single wall polyethylene  
**Temperature:** -40°C to +65°C (-40°F to +150°F)  
**Application:** An extremely flexible and lightweight hose for vacuuming wet or dry materials in shops.

Part Number	ID (in)	Max WP (psi)	Vacuum (hg)	Weight (lb/ft)	Standard Pack
DV30-125	1-¼	13	21"	0.27	50'- Coil
DV30-150	1-½	13	21"	0.25	50'- Coil



## DV40 COMMERCIAL VAC (G VAC)

**Tube:** Black polyethylene  
**Cover:** Blue polyethylene  
**Temperature:** -40°C to +65°C (-40°F to +150°F)  
**Application:** A dual wall polyethylene hose. Ideal for truck mount, car washing & other commercial vacuum application. Smooth interior for better vacuum performance.

Part Number	ID (in)	Max WP (psi)	Vacuum (hg)	Weight (lb/ft)	Standard Pack
DV40-150	1-½	20	29"	0.26	50'- Coil
DV40-200	2	14	29"	0.32	50'- Coil
DV40-300	3	8	29"	0.73	50'- Coil
DV40-400	4	8	29"	1.10	50'- Coil

## DV35 CUFFS



Part Number	ID (in)
DV35-125	1-¼
DV35-150	1-½
DV35-200	2

## DV38 JOINER



Part Number	ID (in)
DV38-125	1-¼
DV38-150	1-½
DV38-200	2

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.