

High Pressure Cleaning

PRESSURE WASH HOSE



- Tube:** Black synthetic rubber
- Reinforcement:** One/Two braids of high tensile steel wire
- Cover:** Smooth Blue, Gray (Yellow – Oil Resistant) abrasion & weather resistant synthetic rubber
- Packaging:** 50',100' and reels
- Application:** Pressure wash equipment.

| Part Number | Cover | Max Temp | | Steam Service | ID in | OD in | Max WP psi | Min BR in | Weight lbs/ft | Coupling |
|-------------|-------|----------|-----|---------------|----------|----------|---------------|--------------|------------------|----------|
| | | °F | °C | | | | | | | |
| PW4000B-04 | Blue | 250 | 121 | No | 1/4 | 0.48 | 4,000 | 3.0 | 0.19 | E |
| PW4000B-06 | Blue | 250 | 121 | No | 3/8 | 0.61 | 4,000 | 4.0 | 0.24 | E |
| PW6000G-06 | Grey | 250 | 121 | No | 3/8 | 0.67 | 6,000 | 6.0 | 0.39 | E |

OIL-RESISTANT COVER

| | | | | | | | | | | |
|------------|--------|-----|-----|----|-----|------|-------|-----|------|---|
| PW4000Y-06 | Yellow | 250 | 121 | No | 3/8 | 0.61 | 4,000 | 4.0 | 0.24 | E |
|------------|--------|-----|-----|----|-----|------|-------|-----|------|---|

| Part Number | Cover | Max Temp | | Steam Service | ID in | Length | Max WP psi | Fitting A | Fitting B |
|------------------|--------|----------|-----|---------------|----------|--------|---------------|-----------|------------|
| | | °F | °C | | | | | | |
| PW4000B-06MMS050 | Blue | 250 | 121 | No | 3/8 | 50' | 4,000 | NPT-Solid | NPT-Swivel |
| PW4000B-06MMS100 | Blue | 250 | 121 | No | 3/8 | 100' | 4,000 | NPT-Solid | NPT-Swivel |
| PW4000Y-06MMS050 | Yellow | 250 | 121 | No | 3/8 | 50' | 4,000 | NPT-Solid | NPT-Swivel |
| PW4000Y-06MMS100 | Yellow | 250 | 121 | No | 3/8 | 100' | 4,000 | NPT-Solid | NPT-Swivel |
| PW6000G-06MMS050 | Grey | 250 | 121 | No | 3/8 | 50' | 4,000 | NPT-Solid | NPT-Swivel |
| PW6000G-06MMS100 | Grey | 250 | 121 | No | 3/8 | 100' | 4,000 | NPT-Solid | NPT-Swivel |






BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.





WB WATERBLAST HOSE

Tube: Black synthetic rubber
Reinforcement: Four spiral wire
Cover: Black abrasion and weather resistant rubber
Temperature: -30°C to +70°C (-22°F to +158°F)
Application: Very high pressure water blasting.

Branding: FORSAFLEX WB15-08 1/2" WATERBLAST
 15000 PSI MAX WP 2.5:1 SAFETY FACTOR

| Part Number |  |  | |  |  |  |
|-------------|---|---|------|--|---|---|
| | ID | OD | | Max WP | Min BR | Weight |
| | in | in | mm | psi | in | lbs/ft |
| WB15-06 | 3/8 | 0.80 | 20.3 | 15,000 | 7.0 | 0.55 |
| WB15-08 | 1/2 | 0.96 | 24.4 | 15,000 | 8.3 | 0.75 |
| WB15-12 | 3/4 | 1.26 | 32.0 | 15,000 | 10.0 | 1.16 |
| WB10-16 | 1 | 1.53 | 38.9 | 10,000 | 11.0 | 1.46 |



| Part Number |  |  | Length | Fitting |
|---------------|--|--|--------|----------|
| | ID | Max WP | | |
| | in | psi | feet | |
| WB15-06-MM006 | 3/8 | 15,000 | 6 | Male NPT |
| WB15-06-MM010 | 3/8 | 15,000 | 10 | Male NPT |
| WB15-06-MM025 | 3/8 | 15,000 | 25 | Male NPT |
| WB15-06-MM050 | 3/8 | 15,000 | 50 | Male NPT |
| WB15-06-MM100 | 3/8 | 15,000 | 100 | Male NPT |
| WB15-08-MM006 | 1/2 | 15,000 | 6 | Male NPT |
| WB15-08-MM010 | 1/2 | 15,000 | 10 | Male NPT |
| WB15-08-MM025 | 1/2 | 15,000 | 25 | Male NPT |
| WB15-08-MM050 | 1/2 | 15,000 | 50 | Male NPT |
| WB15-08-MM100 | 1/2 | 15,000 | 100 | Male NPT |
| WB15-12-MM025 | 3/4 | 15,000 | 25 | Male NPT |
| WB15-12-MM050 | 3/4 | 15,000 | 50 | Male NPT |
| WB15-12-MM100 | 3/4 | 15,000 | 100 | Male NPT |
| WB10-16-MM025 | 1 | 10,000 | 25 | Male NPT |
| WB10-16-MM050 | 1 | 10,000 | 50 | Male NPT |
| WB10-16-MM100 | 1 | 10,000 | 100 | Male NPT |

Other lengths and fitting combinations are available.

Only available as factory coupled & tested assemblies.






BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

High Pressure Cleaning






SEWER CLEANING HOSE



Tube: Yellow olefin
Reinforcement: Synthetic fiber
Cover: Polyurethane - orange for 2500 psi, blue for 3000 psi, green for 4,000 psi, red for 5,000 psi.
Temperature: -40°C to +71°C (-40°F to +160°F)
Packaging: Coils
Application: Sewer Cleaning hose is constructed from materials selected to provide rugged and reliable service under the most severe and demanding conditions found in high pressure sewer cleaning.

| Part Number | Cover |  |  | |  |  |  | Standard Pack |
|-----------------|--------|---|---|------|--|---|---|---------------|
| | | in | in | mm | psi | in | lbs/ft | |
| SCH-2500-16-500 | Orange | 1 | 1.46 | 37.0 | 2,500 | 6.0 | 0.40 | 500' - Roll |
| SCH-2500-16-600 | Orange | 1 | 1.46 | 37.0 | 2,500 | 6.0 | 0.40 | 600' - Roll |
| SCH-2500-16-800 | Orange | 1 | 1.46 | 37.0 | 2,500 | 6.0 | 0.40 | 800' - Roll |
| SCH-3000-16-500 | Blue | 1 | 1.46 | 37.0 | 3,000 | 8.0 | 0.41 | 500' - Roll |
| SCH-3000-16-600 | Blue | 1 | 1.46 | 37.0 | 3,000 | 8.0 | 0.41 | 600' - Roll |

Factory Crimped with Male NPT each end

| Part Number | Cover |  |  | |  |  |  | Standard Pack |
|-------------|-------|---|---|------|---|---|---|---------------|
| | | in | in | mm | psi | in | lbs/ft | |
| SLGR-02 | Green | 1/8 | 0.32 | 8.1 | 4,000 | 1.3 | 0.04 | Coil |
| SLGR-03 | Green | 3/16 | 0.41 | 10.4 | 4,000 | 1.8 | 0.05 | Coil |
| SLGR-04 | Green | 1/4 | 0.50 | 12.7 | 4,000 | 2.5 | 0.06 | Coil |
| SLGR-06 | Green | 3/8 | 0.65 | 16.5 | 4,000 | 3.0 | 0.11 | Coil |
| SLGR-08 | Green | 1/2 | 0.83 | 21 | 4,000 | 4.0 | 0.16 | Coil |
| | | | | | | | | |
| SLRD-04 | Red | 1/4 | 0.50 | 12.2 | 5,000 | 2.5 | 0.05 | Coil |
| SLRD-06 | Red | 3/8 | 0.65 | 16.5 | 5,000 | 3.0 | 0.13 | Coil |

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.