

Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
GX-03	E03	14.0	--	0	U	14	0.0
GX-04	E04	16.8	--	1	H	16	0.8
GX-05	E05	17.8	--	1.5	R	16	1.8
GX-06	E06	20.6	--	2	EE	19	1.6
GX-08	E08	24.2	--	3	R	23	1.2
GX-12	E12	32.0	--	4	S	31	1.0
GX-16	E16	41.1	--	5	LL	39	2.1
GX-20	E20	49.2	--	6	YY	48	1.2
GX-24	E24	56.3	--	--	--	56	0.3
GX-32	E32	69.5	--	--	--	69	0.5
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
GX-06	N06	21.2	--	2	Z	19	2.2
GX-06	N06	21.2	--	2.5	S	19	2.2
GX-08	N08	23.7	--	3	JJ	23	0.7
GX-16	N16	41.3	--	5	LL	39	2.3
GX-20	N20	51.3	--	6	SS	51	0.3
GX-24	N24	60.0	--	--	--	56	4.0
GX-32	N32	73.0	--	--	--	69	4.0
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
AXT-04	E04	16.0	--	1	P	14	2.0
AXT-06	E06	19.6	--	2	V	19	0.6
AXT-08	E08	24.6	--	3	P	23	1.6
AXT-12	E12	31.5	--	4	MM	31	0.5
AXT-16	E16	40.8	--	5	MM	39	1.8
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
AXT-08	N08	23.9	--	3	HH	23	0.9
AXT-12	N12	33.0	--	4.5	SS	31	2.0
AXT-16	N16	39.0	--	5.0	SS	39	0.0

\*\*\*Crimp diameters must be verified with a calibrated caliper\*\*\*

\*\*\*Les diamètres de sertissage doivent être vérifiés avec un vernier calibré\*\*\*

Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
PX260-06	E06	20.4	--	2	GG	19	1.4
PX260-08	E08	24.1	--	3	R	23	1.1
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
EGT-04	E04	17.8	--	1.5	R	16	1.8
EGT-06	E06	22.0	--	2	C	19	3.0
EGT-06	E06	22.0	--	2.5	R	19	3.0
EGT-08	E08	25.5	--	3	C	23	2.5
EGT-10	E10	28.2	--	3.5	KK	27	1.2
EGT-12	E12	32.4	--	4	KK	31	1.4
EGT-16	E16	41.7	--	5	V	39	2.7
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
EX-04	E04	17.0	--	1	H	16	1.0
EX-04	E04	17.0	--	1.5	S	16	1.0
EX-05	E05	19.3	--	1.5	H	19	0.3
EX-06	E06	21.5	--	2	U	19	2.5
EX-06	E06	21.5	--	2.5	KK	19	2.5
EX-08	E08	24.7	--	3	P	23	1.7
EX-10	E10	27.6	--	3.5	LL	26	1.6
EX-12	E12	32.0	--	4	UU	31	1.0
EX-16	E16	41.2	--	5	LL	39	1.7
EX-20	E20	51.8	--	6	RR	51	0.8
EX-24	E24	58.2	--	7	WW	56	2.2
EX-32	E32	71.5	--	--	--	69	2.5
EX-40	HA40	85.2	--	--	--	80	5.2

\*\*\*Crimp diameters must be verified with a calibrated caliper\*\*\*

\*\*\*Les diamètres de sertissage doivent être vérifiés avec un vernier calibré\*\*\*

Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
EX-08	N08	24.9	--	3	Q	23	1.9
EX-10	N10	30.2	--	--	--	27	3.2
EX-12	N12	33.1	--	4.5	SS	31	2.1
EX-16	N16	39.9	--	5	QQ	39	0.9
EX-20	N20	51.9	--	6	RR	51	0.9
EX-24	N24	61.5	--	--	--	56	5.5
EX-32	N32	74.6	--	8	PP	74	0.6
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
PX250-04	E04	17.0	--	1	H	16	1.0
PX250-04	E04	17.0	--	1.5	S	16	1.0
PX250-06	E06	20.6	--	2	EE	19	1.6
PX250-08	E08	24.6	--	3	P	23	1.6
PX250-10	E10	27.3	--	3.5	MM	27	0.3
PX250-12	E12	31.5	--	4	MM	31	0.5
PX250-16	E16	40.8	--	5	MM	39	1.8
PX250-20	E20	49.2	--	6	YY	48	1.2
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
PX250-08	N08	23.9	--	3	HH	23	0.9
PX250-10	N10	29.5	--	--	--	27	2.5
PX250-12	N12	33.0	--	4.5	SS	31	2.0
PX250-16	N16	39.0	--	5	SS	39	0.0
PX250-20	N20	49.2	--	6	YY	48	1.2
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
PX300-04	E04	16.2	--	1	P	16	0.2
PX300-06	E06	20.6	--	2	EE	19	1.6
PX300-08	E08	24.2	--	3	GG	23	1.2
PX300-10	E10	28.2	--	3.5	KK	27	1.2
PX300-12	E12	32.4	--	4	V	31	1.4
PX300-16	E16	40.6	--	5	NN	39	1.6

\*\*\*Crimp diameters must be verified with a calibrated caliper\*\*\*

\*\*\*Les diamètres de sertissage doivent être vérifiés avec un vernier calibré\*\*\*

Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
PX300-06	N06	20.4	--	2	GG	19	1.4
PX300-08	N08	23.6	--	3	JJ	23	0.6
PX300-10	N10	30.4	--	--	--	27	3.4
PX300-12	N12	33.0	--	4.5	SS	31	2.0
PX300-16	N16	39.0	--	5	SS	39	0.0
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
NT300-06	N06	22.0	--	2	C	19	3.0
NT300-08	N08	25.6	--	3	C	23	2.6
NT300-10	N10	31.2	--	4	PP	31	0.2
NT300-12	N12	33.1	--	4.5	SS	31	2.1
NT300-16	N16	40.3	--	5	PP	39	1.3
NT300-20	N20	49.2	--	6	YY	48	1.2
NT300-24	N24	58.7	--	7	RR	56	2.7
NT300-32	N32	73.6	--	8	VV	69	4.6
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
NT300-12	V12	33.1	--	4.5	SS	31	2.1
NT300-16	V16	41.2	--	5.2	SS	39	2.2
NT300-20	VS20	48.0	54.0	--	--	48	0.0
NT300-24	VS24	56.8	73.0	--	--	56	0.8
NT300-32	VS32	72.6	82.6	--	--	69	3.6
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
QX-06HB	N06	21.7	--	2	H	19	2.7
QX-08HB	NL08	27.6	--	3	LL	23	4.6
QX-12HB	N12	34.4	--	4.5	PP	34	0.4
QX-16HB	N16	41.5	--	5	S	39	2.5
QX-20HB	N20	51.3	--	6	SS	51	0.3

\*\*\*Crimp diameters must be verified with a calibrated caliper\*\*\*

\*\*\*Les diamètres de sertissage doivent être vérifiés avec un vernier calibré\*\*\*

Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
VT300-20	VS20	51.5	54.0	6	SS	51	0.5
VT300-24	VS24	58.8	73.0	7	QQ	56	2.8
VT300-32	VS32	76.4	82.6	8	KK	74	2.4
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
CX-08	N08	25.0	--	3	U	23	2.0
CX-10	N10	31.0	--	4	PP	31	0.0
CX-12	V12	34.5	--	4.5	PP	31	3.5
CX-16	V16	41.9	--	5.2	RR	39	2.9
CX-20	VS20	51.3	54.0	6	SS	48	3.3
CX-24	VS24	60.8	73.0	7	KK	56	4.8
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
NZ-20	N20	50.0	--	6	TT	48	2.0
NZ-24	N24	58.7	--	--	--	56	2.7
NZ-32	N32	73.5	--	--	--	69	4.5
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
VZ-24	VS24	61.4	73.0	--	--	56	5.4
VZ-32	VS32	76.0	82.6	--	--	74	2.0
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
QC-06	N06	22.0	--	2	C	19	3.0
QC-06	N06	22.0	--	2.5	HH	19	3.0
QC-08	N08	25.4	--	3	H	23	2.4
QC-10	N10	33.1	--	4	GG	31	2.1
QC-12	N12	35.3	--	4.5	LL	31	4.3
QC-16	N16	41.4	--	5	UU	39	2.4
QC-20	N20	51.9	--	6	RR	48	3.9
QC-24	N24	59.6	67.0	7	NN	56	3.6
QC-32	N32	73.6	80.0	8	VV	69	4.6

\*\*\*Crimp diameters must be verified with a calibrated caliper\*\*\*

\*\*\*Les diamètres de sertissage doivent être vérifiés avec un vernier calibré\*\*\*

Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
VC-12	V12	35.7	--	4.5	S	34	1.7
VC-16	V16	41.5	--	5.2	S	39	2.5
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
CC-12	V12	34.5	--	4.5	PP	31	3.5
CC-16	V16	41.9	--	5.2	RR	39	2.9
CC-20	VS20	53.0	54.0	6	NN	48	5.0
CC-24	VS24	61.7	73.0	7	FF	56	5.7
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
PJ4-04BLM	E04	15.7	--	1	R	14	1.7
PJ4-06BLM	E06	19.6	--	2	V	19	0.6
UJ4-06YWM	E06	19.6	--	2	V	19	0.6
SJ6-06GY	E06	20.6	--	2	EE	19	1.6
SJ7-06BK	E06	20.4	--	2	GG	19	1.4
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
618-02	P02	9.5	--	--	--	8	1.5
618(N)-03	P03	12.6	--	0	JJ	12	0.6
618(N)-04	P04	14.3	--	0	H	14	0.3
618(N)-05	P05	16.0	--	1	P	16	0.0
618(N)-06	P06	17.4	--	1	J	16	1.4
618(N)-08	P08	21.6	--	2	U	19	2.6
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
621-12	390N	32.8	--	4.5	OO	31	1.8
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
625-03	T03	12.7	--	--	--	12	0.7
625-04	T04	14.2	--	0	H	14	0.2
625-06	T06	18.4	--	1.5	P	16	2.4

\*\*\*Crimp diameters must be verified with a calibrated caliper\*\*\*

\*\*\*Les diamètres de sertissage doivent être vérifiés avec un vernier calibré\*\*\*

Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
908BA-04	P04	14.3	--	0	H	14	0.3
908BA-06	P06	17.2	--	1	C	16	1.2
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
908BA-04	T04	14.3	--	0	H	14	0.3
908BA-06	T06	18.4	--	1.5	P	16	2.4
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
HX-12	E12	34.0	--	4	H	31	3.0
HX-16	E16	44.0	--	5	J	39	5.0
HX-20	E20	51.2	--	6	SS	48	3.2
HX-24	E24	59.8	--	7	NN	56	3.8
HX-32	E32	69.8	--	--	--	69	0.8
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
HX-12	N12	35.3	--	4.5	N	34	1.3
HX-16	N16	41.9	--	5	HH	39	2.9
HX-20	N20	52.1	--	6	RR	48	4.1
HX-24	N24	61.0	--	7	KK	56	5.0
HX-32	N32	73.3	--	8	VV	69	4.3
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
J3-04	AF04	16.2	--	1	P	16	0.2
J3-06	AF06	20.3	--	2	R	19	1.3
J3-08	AF08	23.4	--	3	KK	23	0.4
J3-10	AF10	27.2	--	3.5	NN	27	0.2
J3-12	AF12	31.0	--	4	QQ	31	0.0
J3-16	AF16	37.6	--	5	TT	34	3.6

\*\*\*Crimp diameters must be verified with a calibrated caliper\*\*\*

\*\*\*Les diamètres de sertissage doivent être vérifiés avec un vernier calibré\*\*\*

Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
FH-04 - FX-04	F04	16.4	--	1	Q	16	0.4
FH-05 - FX-05	F05	17.5	--	1	J	16	1.5
FH-06 - FX-06	F06	19.9	--	1.5	N	19	0.9
FH-08 - FX-08	F08	21.9	--	2	C	19	2.9
FH-10 - FX-10	F10	26.0	--	3	N	23	3.0
FH-12 - FX-12	F12	30.1	--	3.5	H	27	3.1
FH-16 - FX-16	F16	34.0	--	4.5	PP	31	3.0
FH-20 - FX-20	F20	41.6	--	5	V	39	3.0
FH-24 - FX-24	F24	48.8	--	--	--	48	0.8
FH-32 - FX-32	F32	60.8	--	--	--	56	4.8
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
ZX-06	Z06	16.7	--	--	--	AC-06	
ZX-08	Z08	21.0	--	--	--	AC-08	
ZX-10	Z10	22.7	--	--	--	AC-10	
ZX-12	Z12	25.8	--	--	--	AC-12	
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
HJ-04	E04	17.8	--	1.5	R	16	1.8
HJ-06	E06	21.5	--	2.5	KK	19	2.5
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
FSH-04	E04	16.8	--	1	H	16	0.8
FSH-06	E06	20.6	--	2	EE	19	1.6
FSH-08	E08	24.2	--	3	R	23	1.2
FSH-12	E12	32.0	--	4	S	31	1.0
FSH-16	E16	40.6	--	5	NN	39	1.6

\*\*\*Crimp diameters must be verified with a calibrated caliper\*\*\*

\*\*\*Les diamètres de sertissage doivent être vérifiés avec un vernier calibré\*\*\*



Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
TBR-03	T03	12.0	--	0	S	12	0.0
TBR-04	T04	12.7	--	0	JJ	12	0.7
TBR-05	T05	15.1	--	1	KK	14	1.1
TBR-06	T06	17.3	--	1.5	V	16	1.3
TBR-08	T08	20.8	--	2	P	19	1.8
TBR-10	T10	25.6	--	3	C	23	2.6
TBR-12	T12	28.1	--	3.5	S	27	1.1
TBR-16	T16	35.0	--	4.5	MM	31	4.0
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
TBR-03	TS03	11.4	--	0	MM	10	1.4
TBR-04	TS04	13.2	--	0	EE	12	1.2
TBR-05	TS05	14.2	--	0	H	14	0.2
TBR-06	TS06	15.7	--	1	EE	14	1.7
TBR-08	TS08	20.8	--	2	P	19	1.8
TBR-12	TS12	26.3	--	3	B	24	2.3
TBR-16	TS16	34.4	--	4	C	31	3.4
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
TBX-04C	T04	12.7	--	--	--	12	0.7
TBX-05C	T05	15.1	--	1	KK	14	1.1
TBX-06C	T06	17.3	--	1.5	V	16	1.3
TBX-08C	T08	20.8	--	2	P	19	1.8
TBX-10C	T10	25.6	--	3	C	23	2.6
TBX-12C	T12	29.3	--	3.5	P	27	2.3
TBX-16C	T16	35.0	--	4.5	MM	31	4.0
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
TBX-04C	TS04	12.9	--	0	HH	12	0.9
TBX-05C	TS05	13.9	--	0	U	12	1.9
TBX-06C	TS06	15.7	--	1	EE	14	1.7
TBX-08C	TS08	20.8	--	2	P	19	1.8

\*\*\*Crimp diameters must be verified with a calibrated caliper\*\*\*

\*\*\*Les diamètres de sertissage doivent être vérifiés avec un vernier calibré\*\*\*

Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
AH30-025	AF04	16.4	--	1	Q	16	0.4
AH30-038	AF06	21.6	--	2	H	19	2.6
AH30-050	AF08	24.8	--	3	U	23	1.8
AH30-075	AF12	32.9	--	4.5	SS	31	1.9
AH30-100	AF16	41.5	--	5	V	39	2.5
Hose	Couplings	Crimp Diameter (mm)	Skive Length (mm)	FX17 / FX21		Metric Adjustable	
				Die	Ring	Die	Setting
AH30-025	E04	17.0	--	1	H	16	1.0
AH30-038	E06	21.3	--	2	U	19	2.3
AH30-050	E08	25.4	--	3	C	23	2.4
AH30-075	N12	34.5	--	4.5	NN	31	3.5
AH30-100	E16	43.1	--	5	U	39	4.1
AH30-125	E20	49.8	--	6	TT	48	1.8
AH30-150	E24	57.6	--	--	--	56	1.6

\*\*\*Crimp diameters must be verified with a calibrated caliper\*\*\*

\*\*\*Les diamètres de sertissage doivent être vérifiés avec un vernier calibré\*\*\*