

## Pressure Wash Hose



**Tube:** Black synthetic rubber  
**Reinforcement:** One/Two braids of high tensile steel wire  
**Cover:** Smooth Blue, Gray (Yellow - Oil Resistant) Abrasion resistant synthetic rubber  
**Packaging:** Coils, reels



Part Number	Cover	Max Temp		Steam Service							One Piece Coupling
		°F	°C		in	in	psi	in	mm	lbs/ft	
PW4000B-04	Blue	250	121	No	¼	0.48	4,000	3	76.2	0.19	E
PW4000B-06	Blue	250	121	No	¾	0.61	4,000	4	101.6	0.24	E
PW6000G-06	Gray	250	121	No	¾	0.67	6,000	6	152.4	0.39	E
<b>OIL-RESISTANT COVER</b>											
PW4000Y-06	Yellow	250	121	No	¾	0.61	4,000	4	101.6	0.24	E

## Pressure Wash Assemblies

Part Number	Cover	Max Temp		Steam Service		Length		Fitting A	Fitting B
		°F	°C		in		ft		
PW4000B-06MMS50	Blue	250	121	No	¾	50'	4,000	NPT-Solid	NPT-Swivel
PW4000B-06MMS100	Blue	250	121	No	¾	100'	4,000	NPT-Solid	NPT-Swivel
PW4000Y-06MMS50	Yellow	250	121	No	¾	50'	4,000	NPT-Solid	NPT-Swivel
PW4000Y-06MMS100	Yellow	250	121	No	¾	100'	4,000	NPT-Solid	NPT-Swivel
PW4000G-06MMS50	Gray	250	121	No	¾	50'	6,000	NPT-Solid	NPT-Swivel
PW4000G-06MMS100	Gray	250	121	No	¾	100'	6,000	NPT-Solid	NPT-Swivel

\* Includes two bend restrictors

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

## Steam Cleaner Hose - 2 Wire



**Tube:** Black synthetic rubber  
**Reinforcement:** Two braids of high tensile steel wire  
**Cover:** Smooth black oil and abrasion resistant synthetic rubber  
**Packaging:** Reels


### STEAM SERVICE - UP TO 325°F (163°C)

Part Number	Hose ID		Hose OD		Max WP	Min BR		Weight	Two Piece Ferrule	Two Piece Insert
	in	mm	in	mm	psi	in	mm	lbs/ft		
SK20-06	3/8	14.8	0.58	14.8	350	4.0	101.6	0.28	SK20-06F	SK06
SK20-08	1/2	20.4	0.80	20.4	350	4.5	114.3	0.35	SK20-08F	SK08


### PRESSURE WASH - UP TO 250°F (121°C)

Part Number	Hose ID		Hose OD		Max WP	Min BR		Weight	Two Piece Ferrule	Two Piece Insert
	in	mm	in	mm	psi	in	mm	lbs/ft		
SK20-06	3/8	14.8	0.58	14.8	6,000	4.0	101.6	0.28	SK20-06F	SK06
SK20-08	1/2	20.4	0.80	20.4	6,000	4.5	114.3	0.35	SK20-08F	SK08

### SK20 No Skive Ferrule



Part Number	Hose ID	D	L
	in	mm	mm
SK2-06F	3/8	25.0	28.0
SK2-08F	1/2	28.0	28.0



### MP NPT Male

Part Number	Hose ID	F	H		L		S	
	in		mm	in	mm	mm	in	
SK06-06MP	3/8	3/8 - 18	28.6	1.12	59.1	2.33	19	3/4
SK08-08MP	1/2	1/2 - 14	35.0	1.38	68.0	2.68	22	7/8

#### ⚠ WARNING!

•Only rigid male NPT SK series inserts with SK20F ferrules are approved with steam cleaner hose.

## WB Waterblast Hose



**Tube:** Black synthetic rubber  
**Reinforcement:** Four spiral wire  
**Cover:** Black abrasion and weather resistant rubber  
**Packaging:** Coils



Part Number	ID		OD		Max WP	Min BR	Weight
	in	mm	in	mm	psi	in	lbs/ft
WB15-06	3/8	9.5	0.80	20.3	15,000	7.0	0.55
WB15-08	1/2	12.7	0.96	24.4	15,000	8.3	0.75
WB15-12	3/4	19.0	1.26	32.0	15,000	10.0	1.16
WB10-16	1	25.4	1.53	38.9	10,000	11.0	1.46

Other lengths and fitting combinations are available.  
 Only available as factory coupled & tested assemblies.

1

Pressure Wash Hose



Part Number	ID	Max WP	Length	Fitting
	in	psi	feet	
WB15-06-MM006	3/8	15,000	6	Male NPT
WB15-06-MM010	3/8	15,000	10	Male NPT
WB15-06-MM025	3/8	15,000	25	Male NPT
WB15-06-MM050	3/8	15,000	50	Male NPT
WB15-06-MM100	3/8	15,000	100	Male NPT
WB15-08-MM006	1/2	15,000	6	Male NPT
WB15-08-MM010	1/2	15,000	10	Male NPT
WB15-08-MM025	1/2	15,000	25	Male NPT
WB15-08-MM050	1/2	15,000	50	Male NPT
WB15-08-MM100	1/2	15,000	100	Male NPT
WB15-12-MM025	3/4	15,000	25	Male NPT
WB15-12-MM050	3/4	15,000	50	Male NPT
WB15-12-MM100	3/4	15,000	100	Male NPT
WB10-16-MM025	1	10,000	25	Male NPT
WB10-16-MM050	1	10,000	50	Male NPT
WB10-16-MM100	1	10,000	100	Male NPT

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.